



CANOPY TARP INSTALLATION INSTRUCTIONS

- Loosen set screws on sliding end of canopy frame at the back of the boat.
- Slide canopy end into frame to make frame shorter.
- Lift tarp up on top of frame, rest on center ridge tube.
- Starting at one end, roll tarp down the center of frame.
- Fold tarp out to each side.
- Pull tarp down over each end.
- Position tarp evenly on canopy frame.
- Slide the canopy end out, making the tarp fit snug. **DO NOT over-stretch cover.** If you over-stretch canopy tarp, you will rip out seams at corners.
- Tighten the set screws with $\frac{3}{4}$ " wrench until the bolts are snug.
- Lace elastic cord through the D-rings around the perimeter. Cord should go to the outside of the canopy arms.
- Stretch the ends of the cord to meet and tie ends at one D-ring.
- Hook one end of s-hooks to the elastic cord, and then hook the other end of the hook to the aluminum angle on the canopy frame.
- Place hooks between each D-ring on sides and at least three hooks on each end.

TARP MUST BE REMOVED DURING WINTER MONTHS TO PREVENT DAMAGE TO FRAME AND TARP. CANOPY FRAME IS NOT DESIGNED TO HANDLE A SNOW LOAD. WASH AND DRY TARP THOROUGHLY, THEN FOLD AND STORE INDOORS AWAY FROM RODENTS. RODENTS WILL EAT HOLES THROUGH TARP IF NOT STORED PROPERLY.

READ YOUR OWNER'S MANUAL FOR ADDITIONAL INSTRUCTIONS ON INSTALLING CANOPY FRAME.

